

# STORMFORCE (DP) TERRACE DOOR ELEVATIONS

## 23 5/8" (600 MM) – 70 7/8" (1800 MM) DOOR

| Rough Opening                                | in.                  | 25              | 31 7/8               | 35 1/8               | 37 3/4               | 60 7/16              | 66 15/16             | 72 1/4               |                                    |                      |                      |                                    |                      |                      |                                   |
|--|----------------------|-----------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------------------------------|----------------------|----------------------|------------------------------------|----------------------|----------------------|-----------------------------------|
|  | mm                   | 635             | 809                  | 892                  | 959                  | 1535                 | 1701                 | 1835                 |                                    |                      |                      |                                    |                      |                      |                                   |
| Unit O.S.M.                                  | in.                  | 23 5/8          | 30 1/2               | 33 3/4               | 36 3/8               | 59 1/16              | 65 9/16              | 70 7/8               |                                    |                      |                      |                                    |                      |                      |                                   |
|  | mm                   | 600             | 774                  | 857                  | 924                  | 1500                 | 1666                 | 1800                 |                                    |                      |                      |                                    |                      |                      |                                   |
| <b>6 9/16" (166 mm) with jamb extensions</b> |                      |                 |                      |                      |                      |                      |                      |                      |                                    |                      |                      |                                    |                      |                      |                                   |
| 80 3/8<br>2042                               | 79 1/2<br>2020       |                 |                      |                      |                      |                      |                      |                      | 63 7/8<br>1623<br>64 13/16<br>1647 |                      |                      |                                    |                      |                      |                                   |
|  |                      | TD1 0620        | TD1 0720<br>R L or F | TD1 0820<br>R L or F | TD1 0920<br>R L or F | TD2 1520<br>RF or FL | TD2 1620<br>RF or FL | TD2 1820<br>RF or FL |                                    |                      |                      |                                    |                      |                      |                                   |
|  |                      | 82 3/16<br>2087 | 81 5/16<br>2065      |                      |                      |                      |                      |                      |                                    |                      |                      | 65 11/16<br>1668<br>66 5/8<br>1692 |                      |                      |                                   |
|  |                      |                 |                      | TD1 0621<br>R L or F | TD1 0721<br>R L or F | TD1 0821<br>R L or F | TD1 0921<br>R L or F | TD2 1521<br>RF or FL |                                    | TD2 1621<br>RF or FL | TD2 1821<br>RF or FL |                                    |                      |                      |                                   |
|  |                      |                 |                      | 86 7/8<br>2206       | 86<br>2184           |                      |                      |                      |                                    |                      |                      |                                    |                      |                      | 70 3/8<br>1787<br>71 5/16<br>1811 |
|  |                      |                 |                      |                      |                      | TD1 0670<br>R L or F | TD1 0770<br>R L or F | TD1 0870<br>R L or F |                                    | TD1 0970<br>R L or F | TD2 1570<br>RF or FL |                                    | TD2 1670<br>RF or FL | TD2 1870<br>RF or FL |                                   |
|  |                      |                 |                      |                      |                      | 95 3/8<br>2422       | 94 1/2<br>2400       |                      |                                    |                      |                      |                                    |                      |                      |                                   |
| TD1 0624<br>R L or F                         | TD1 0724<br>R L or F |                 |                      |                      |                      |                      |                      | TD1 0824<br>R L or F | TD1 0924<br>R L or F               | TD2 1524<br>RF or FL | TD2 1624<br>RF or FL |                                    | TD2 1824<br>RF or FL |                      |                                   |
| in.  | 13 1/16              |                 |                      |                      |                      |                      |                      | 19 15/16             | 23 3/16                            | 25 13/16             | 19 15/16             |                                    | 23 3/16              | 25 13/16             |                                   |
| mm   | 332                  | 506             | 589                  |                      |                      |                      |                      | 656                  | 506                                | 589                  | 656                  |                                    |                      |                      |                                   |
| in.  | 14 1/16              | 20 7/8          | 24 3/16              |                      |                      |                      |                      | 26 13/16             | 20 7/8                             | 24 3/16              | 26 13/16             | Glass<br>Size                      |                      |                      |                                   |
| mm   | 357                  | 531             | 614                  | 681                  | 531                  |                      |                      | 614                  | 681                                |                      |                      |                                    |                      |                      |                                   |

**Note:** • Grille pattern dependent on grille type.  
• All information is subject to HP1 glazing.



StormForce

*Loewen*

N47

www.loewen.com